

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
26 April 2001 (26.04.2001)

PCT

(10) International Publication Number
WO 01/29158 A1

(51) International Patent Classification⁷: C10M 169/00 //
(C10M 169/00, 101:02, 103:00, 103:02, 103:06, 113:00,
113:02, 113:08, 113:10, 119:02, 125:02, 125:22, 125:26,
125:30, 159:06), C10N 20:06, 30:06

Chaikovskogo, 33b/53, Kharkov, 61024 (UA). GAMI-
DOV, Elmin Abbas-ogli [UA/UA]; Groznenskaya ul.,
56/39, Kharkov, 61124 (UA). ZOZULYA, Vladimir
Leonidovich [UA/UA]; ul. Bakulina, 1/9/10, Kharkov,
61054 (UA). ZOZULYA, Sergei Leonidovich [UA/UA];
Sumgaitskaya ul., 4/3, Kharkov, 61018 (UA).

(21) International Application Number: PCT/UA00/00035

(22) International Filing Date: 5 October 2000 (05.10.2000)

(74) Agent: SERJUGINA, Alla Sergeevna; ul. Pavlika Moro-
zova, 2/12, a/ya 9428, Kharkov, 61108 (UA).

(25) Filing Language: English

(81) Designated States (*national*): AE, AM, AT, AU, AZ, BA,
BG, BR, BY, CA, CH, CN, CZ, DE, EE, ES, FI, GB, GE,
HU, IL, IN, JP, KG, KP, KR, KZ, LT, LU, LV, MD, MK,
MN, MX, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TM,
TR, US, UZ, VN, YU, ZA.

(26) Publication Language: English

(30) Priority Data:
99105787 22 October 1999 (22.10.1999) UA


Published:

— With international search report.

(71) Applicants and

(72) Inventors: ALEXANDROV, Sergei Nikolaevich
[UA/UA]; ul. 2-oi Pyatiletki, 18/54, Kharkov, 61007
(UA). BUZOV, Vladimir Valentinovich [UA/UA]; ul.

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.



WO 01/29158 A1

(54) Title: LUBRICANT COMPOSITION

(57) Abstract: The present invention relates to lubricant compositions and can be used for treatment of friction units in different machines and mechanisms in manufacturing processes, the purpose of which is modification of friction surfaces. The basis of the invention is the improvement of lubricant composition, in which as the consequence of the additional use of thickener and wax, the viscosity of lubricant composition sufficient for conversation of uniform distribution of solid component in lubricant composition in broad temperature range is provided; and at the expense of that, the possibility of conservation of lubricant composition in any packaging and bulks, which are usable even under operating conditions of machines and mechanisms, is reached. The lubricant composition acquires the state of gel, that is convenient to put on any friction surface, to deposit on a zone of friction of any friction units. The lubricant composition ensures the receiving of engineering results similar to those, which solid components exhibit using fine-dispersed powder on basis of natural minerals from flaky silicates series and at the same time the sedimentation properties of lubricant composition permit its continuous conservation in broad temperature range without variation of lubrication and modification properties.